



Innovation

- Unique sliding stainless canopy can be pushed back against the wall for increased head room
- 45% increase in capture area when hood is extended

Performance

- 600 CFM Integrated Blower included
- Three fan speeds plus 10 minute high-power operation mode
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- Delayed shut off tackles lingering odors for up to 10 minutes
- Dimmer lighting - for those hours after a late meal
- Dishwasher safe stainless-frame mesh filters
- Filter systems are highly efficient at capturing grease
- Powerfully quiet ventilation systems
- Sound insulation mats make this hood barely audible
- 6" Round duct size
- Vertical ducting direction
- Telescopic chimney - adjustable at installation
- Hood includes filters, backdraft damper and transition

Design

- Brushed stainless steel finish
- Welded, polished seams for a flawless design
- Premium electronic touch controls
- Halogen lighting spotlights your best recipes

Frequency (Hz)	60
Approval certificates	ETL
Plug type	120V-3 prong
Height of the chimney (in)	23 7/8" - 39 5/8"
Net weight (lbs)	64
Gross weight (lbs)	82
Required distance above range/rangetop/cooktop	30"/30"
Motor location	Integrated motor in hood chimney
Diameter of air duct (in) top	6
Operating mode	Ducted
Delay shut off modes	10
Optional accessories	CHIMXHDD
Number of lights	4
Type of lamps used	Halogen
Total power of the lamps (W)	80
Grease filter material	Washable aluminium
Grease filter type	Multilayer cassette