



Performance

- Recirculation possible with kit RECIRC__FS (max 600CFM)
- Three fan speeds plus 10 minute high-power operation mode
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- Delayed shut off tackles lingering odors for up to 10 minutes
- Dishwasher safe hybrid mesh filters
- Filter systems are highly efficient at capturing grease
- Powerfully Quiet® ventilation systems
- 10" Round duct size
- Vertical ducting direction
- Hood includes filters, lights, backdraft damper and transition
- Blowers sold separately
- Choose from Inline, Remote or Integrated Blowers
- Accessories include: Stainless steel duct covers in 6" or 12" heights
- Replacement charcoal filters available (CHFILT3036)

Design

- Brushed stainless steel finish
- Welded, polished seams for a flawless design
- Premium electronic touch controls
- Halogen lighting spotlights your best recipes

Amps (A)	15
Frequency (Hz)	60
Approval certificates	CSA, UL
Plug type	fixed connection
Net weight (lbs)	35
Gross weight (lbs)	48
Required distance above range/rangetop/cooktop	30"/30"
Motor location	without motor
Diameter of air duct (in) top	10
Discharge direction	vertical
Operating mode	Convertible: Ducted / Recirculating
Delay shut off modes	15M
Optional accessories	CHFILT3036, DC30US, DCT30US, PA30JBS, RECIRC30FS, RFPLT1000, RFPLT600
Number of lights	2
Type of lamps used	Halogen
Total power of the lamps (W)	100
Grease filter material	Washable stainless steel
Grease filter type	Multilayer cassette