



### **Performance**

- 600 CFM Integrated Blower included
- Recirculation possible with kit RECIRISL
- Three fan speeds
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- Delayed shut off tackles lingering odors for up to 10 minutes
- Dishwasher safe frameless filters with stainless steel covers
- Filter systems are highly efficient at capturing grease
- Powerfully quiet ventilation systems
- 6" Round duct size
- Vertical ducting direction
- All-in-one solution with an integral blower included
- Hood includes filters, backdraft damper and transition
- Replacement charcoal filters available (CHFILSL)

### **Design**

- Sleek appearance does not obstruct views beyond the kitchen
- Brushed stainless steel finish
- Chiseled design for a seamless integration into any kitchen
- Halogen lighting spotlights your best recipes
- Stainless steel control buttons

Amps (A)	5
Frequency (Hz)	60
Approval certificates	ETL
Plug type	120V-3 prong
Height of the chimney (in)	28 3/8" - 39 7/16"
Net weight (lbs)	96
Gross weight (lbs)	116
Required distance above range/rangetop/cooktop	30"/30"
Motor location	Integrated motor in hood chimney
Diameter of air duct (in) top	6
Operating mode	Convertible: Ducted / Recirculating
Delay shut off modes	10
Optional accessories	CHFILISL, RECIRISL
Number of lights	4
Type of lamps used	Halogen
Total power of the lamps (W)	80
Grease filter material	Washable stainless steel
Grease filter type	Multilayer cassette