



Performance

- 600 CFM Integrated Blower included
- Recirculation possible with kit RECIRISL
- Three fan speeds
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- Delayed shut off tackles lingering odors for up to 10 minutes
- Dishwasher safe frameless filters with stainless steel covers
- Filter systems are highly efficient at capturing grease
- Powerfully quiet ventilation systems
- 6" Round duct size
- Vertical ducting direction
- All-in-one solution with an integral blower included
- Hood includes filters, backdraft damper and transition
- Replacement charcoal filters available (CHFILSL)

Design

- Sleek appearance does not obstruct views beyond the kitchen
- Brushed stainless steel finish
- Chiseled design for a seamless integration into any kitchen
- Halogen lighting spotlights your best recipes
- Stainless steel control buttons

| | |
|--|-------------------------------------|
| Amps (A) | 5 |
| Frequency (Hz) | 60 |
| Approval certificates | ETL |
| Plug type | 120V-3 prong |
| Height of the chimney (in) | 28 3/8" - 39 7/16" |
| Net weight (lbs) | 96 |
| Gross weight (lbs) | 116 |
| Required distance above range/rangetop/cooktop | 30"/30" |
| Motor location | Integrated motor in hood chimney |
| Diameter of air duct (in) top | 6 |
| Operating mode | Convertible: Ducted / Recirculating |
| Delay shut off modes | 10 |
| Optional accessories | CHFILISL, RECIRISL |
| Number of lights | 4 |
| Type of lamps used | Halogen |
| Total power of the lamps (W) | 80 |
| Grease filter material | Washable stainless steel |
| Grease filter type | Multilayer cassette |